




DIAL INDICATORS



Gagemaker's mechanical indicators are manufactured per ANSI AGD specifications. Standard indicators used in Gagemaker products are made in the U.S.A.

Accuracy
Per AMSI B89.1.10M-1987

Model	Correlating Gage Model	Travel/Resolution	First 2 1/3 Rev	After 2 1/3 Rev
801 (BAL)	BR-2001	.250"/.001"	±.001"	±.002"
8011 (BAL)	TH-3002R, TH-3002V	.250"/.001"	±.001"	±.002"
802 (CONT)	WT-9000 Series	.250"/.001"	±.001"	±.002"
8021 (CONT)	TH-3001R, TH-3001V, PD-3003	.250"/.001"	±.001"	±.002"
803 (BAL)	PN-3000 Series, BX-1000, BXG-1000	.125"/.0005"	±.0005"	±.001"
8031 (BAL)	TH-3002B, TH-3003B, TS-4000	.125"/.0005"	±.0005"	±.001"
862L (CONT)	ET-7000 Series with Lever	.500"/.001"	±.001"	±.002"
8621 (CONT)	IT-6001, PD-3004	.500"/.001"	±.001"	±.002"
863	RG-7000 Series, TH-3004, TH-3006, TH-3008, TH-3009, TH-3010, SRG-7000, CA-9001, MRP-5000 Series, SPG-6000	.500"/.0005"	±.0005"	±.001"
863L (BAL)	PD-8000 Series w/ Lever	.500"/.0005"	±.0005"	±.001"
8631 (BAL)	PD-6000, PD-6001, PG-6000 Series, TS-1000, IT-5100, MRP-5500, SPG-6000	.500"/.0005"	±.0005"	±.001"
882L (CONT)	ET-7003, ET-7005, ET-7007	1.00"/.001"	±.001"	±.002"
8821 (CONT)	IT-6000	1.00"/.001"	±.001"	±.002"
80-0403	LG-5002, LG-5003	.100"/.0005"	±.0005"	±.001"
80-0400	LG-5002, LG-5003	.025"/.0001"	±.0001"	±.0003"
83-0584	MRP-2000, MRP-2500, MRP-3000	.500"/.001"	±.001"	±.002"
83-0582	MRP-2000, MRP-2500, MRP-3000	.500"/.0005"	±.0005"	±.001"
87-070	MRP-1000, MRP-1500	.125"/.0005"	±.0005"	±.001"

*Note: I after the model number indicates counter clockwise rotation.
L after model number indicates a lifting lever.*

DIAL INDICATORS*

Model	Description	Travel/Res.	First 2 1/3 Rev	After 2 1/3 Rev
805 (BAL)	General Application Mechanical	.100"/.0005"	±.0005"	±.001"
2358B-MRP	All MRP Gages	.500"/.0001"	±.0001"	±.0003"
2358SGA	General Application Mechanical	.500"/.0001"	±.0001"	±.0003"
2358SRGA	General Application Mechanical	.500"/.0001"	±.0001"	±.0003"
2776FB	General Application Mechanical	1.00"/.0005"	±.0005"	±.002"

METRIC DIAL INDICATORS*

Model	Description	Travel/Res.	First 2 1/3 Rev	After 2 1/3 Rev
1044SRGA (CONT)	Metric Mechanical	5 mm/.01 mm	±.01 mm	±.02 mm
1045SGA (BAL)	Metric Mechanical	5 mm/.01 mm	±.01 mm	±.02 mm
2047SGA (BAL)	Metric Mechanical	10 mm/.01 mm	±.01 mm	±.02 mm
2046SGA (CONT)	Metric Mechanical	10 mm/.01 mm	±.01 mm	±.02 mm
2902SRGA (CONT)	Metric Mechanical	10 mm/.01 mm	±.01 mm	±.02 mm

DIGITAL INDICATORS*

Model	Description	Travel/Res.	First 2 1/3 Rev	After 2 1/3 Rev
543-683B	Electronic/Digital	.500"/.0005"	±.0005"	±.001"

*Indicators for special applications require calling for a quotation.